Upgraded version of X2
Brushless Motor
Improved PC Board
Greater Durability
Higher Efficiency
Maintenance-free
Noise-free

MINI MILLING MACHINE

Specifications

Drilling capacity	13 mm
End milling capacity	16 mm
Face milling capacity	30 mm
Headstock travel (Z)	180 mm
Cross axis (X)	100 mm
Longitudinal axis (Y)	220 mm
Throat	170 mm
Max. distance spindle to table	280 mm
Head tilt	45°L, 45°R
Spindle taper	MT3 or R8
Spindle speed	100-2500 rpm±10%
Motor output power(Brushless motor)	500 W
Table effective size	385x100 mm
T-slot size	12 mm
Overall dimension (LxWxH)	520x500x760 mm
Weight (Net/Gross)	50/68 kg
Packing size (LxWxH)	540x540x760 mm

Standard attachment

Ø13 mm Drill chuck
Wrench set
Oil can

OPTIONAL ACCESSORIES

Stub milling machine arbor

MT#3
for slitting saw,hole ø16 mm
S/N:10127

Boring arbor with boring cutter

MT#3
S/N:10128

Stub milling machine arbor

MT#3
for slitting saw,hole ø1 mm
S/N:10129

2 Flute HSS end mill

ø4mm	S/N:10038
ø6mm	S/N:10039
ø8mm	S/N:10040
ø10mm	S/N:10041
ø12mm	S/N:10042
ø14mm	S/N:10043
ø16mm	S/N:10044
ø4-16mm set	S/N:10045

MT#3 collet

ø4mm	S/N:10119
ø6mm	S/N:10120
ø8mm	S/N:10121
ø10mm	S/N:10122
ø12mm	S/N:10123
ø14mm	S/N:10124
ø16mm	S/N:10125
ø4-16mm set	S/N:10126

Digital spindle speed readout

S/N:10030
For mini mill SX2

Mill chuck set

MT#3
Chuck dia. 4,6,8,10,12,14,16mm

S/N:10037

vice

Width 80mm

S/N:10109