MINI MILLING MACHINE

Specifications

Drilling capacity		13 mm
End milling capacity		16 mm
Face milling capacity		30 mm
Headstock travel (Z)		180 mm
Cross axis (X)		100 mm
Longitudinal axis (Y)		220 mm
Throat		170 mm
Max. distance spindle to table		280 mm
Head tilt		45°L, 45°R
Spindle taper		MT3 or R8
Motor output power		350 W
Spindle speed	Low range	100-1100 rpm±10%
	High range	100-2500 rpm±10%
Table effective size		390x92 mm
T-slot size		12 mm
Overall dimension (LxWxH)		520x500x760 mm
Weight (Net/Gross)		50/68 kg
Packing size (LxWxH)		520x520x730 mm

X2A is a X2 with Auto-feed.

Standard attachment

Ø13 mm Drill chuck
Wrench set
Oil can

Now X2 ⇨ UPGRADE to ⇨ Super X2

OPTIONAL ACCESSORIES

Rotary table

Size 100mm

S/N: 10094

Dividing Plate for S/N 10094

S/N: 10094-1

Tailstock for S/N 10094

S/N: 10094-2

Quick vice

Width 100mm

S/N:10036

Auto feeder

You can mount this Auto feeder on X2 yourself!

S/N:10132

Indexable carbide end mill

MT#3
ø30mm

S/N:10046

Clamping kit

42 pcs.
Bolt size:10mm
include:12 studs, 6 step block pairs, 4 T nuts, 4 flange nuts, 4 coupling nuts, 6 end holddowns

S/N:10047