

MINI LATHE

Specifications

Swing over bed		180 mm
Cross slide travel		65 mm
Motor output power		350 W
Distance between centers		350 mm
Hole through spindle		20 mm
Spindle taper		MT3
Tailstock taper		MT2
Spindle speed	Low range	100-1200 rpm±10%
	High range	100-3000 rpm±10%
Thread range	Metric version	0.4-2.0 mm (5 threads pitches)
	Imperial version	12-52 TPI (5 threads pitches)
Overall dimension (LxWxH)		880x290x290 mm
Weight (Net/Gross)		44/56 kg
Packing Size (LxWxH)		870x360x380 mm

Standard attachment

- 80mm 3-jaw Chuck
- MT2 Center
- Changing gear set
- Wrench set
- Oil can



C3A is C3 with DRCD

OPTIONAL ACCESSORIES

Cutter 11 pieces set

- DIN 4971R DIN 4972R
- DIN 4973R DIN 4974R
- DIN 4975 DIN 4976
- DIN 4977R
- DIN 4978R
- DIN 4980L
- DIN 4980R
- DIN 4981R



8X8mm S/N:10005



C2 or C3 owner, replace to DRCD by yourself.

Digital readout for cutting depth kit (DRCD kit)



S/N:10140

3-jaw chuck



S/N:10100 ø100mm
S/N:10100A ø100mm with flange

4-jaw chuck (independent)



S/N:10010 ø80mm
S/N:10029 ø100mm
S/N:10029A ø100mm with flange

Spindle center



MT#3
S/N:10013

Rolling center



MT#2
S/N:10014

Lathe dog



S/N:10015

Steady rest



S/N:10008

Follow rest




S/N:10009

Face plate




ø160mm
S/N:10007

Clamping kit for face plate



S/N:10007A




Workshop Practice Series book "The Mini-Lathe" (Or get one free for every purchase of 5 pieces C3)

S/N:10031

Rolling tailstock chuck



Dia. 13mm+MT#2
S/N:10147



Mill chuck set



Chuck dia. 4, 6, 8, 10, 12, 14, 16mm



S/N:10148

Check C2 for other Optional Accessories