

Upgraded version of C2
Brushless Motor
Improved PC Board
Greater Durability
Higher Efficiency
Maintenance-free
Noise-free



MINI LATHE Model 300

Specifications

Swing over bed	180 mm
Swing over saddle	110 mm
Distance between centers Model 300	300 mm
Hole through spindle	20 mm
Cross slide travel	65 mm
Spindle taper	MT3
Tailstock taper	MT2
Spindle speed	100-2500 rpm ± 10%
Motor output power (Brushless motor)	500 W
Range of threads Metric version 0.4-2.0 mm (10 thread pitches)	
Imperial version 12-52 TPI (8 thread pitches)	
Overall dimension (LxWxH)	720x300x290 mm
Weight (Net/Gross)	50/60 kg
Packing size (LxWxH)	870x360x380 mm



No more High/Low Gear Trouble Free



Digital Spindle Speed Readout Available (Optional) S/N: 10030

Standard attachment

- 80mm 3-jaw Chuck
- MT2 Center
- Change gear set
- Wrench set
- Oil can

Features

- Safety Switch
- Variable speed
- Four position turret post
- High accuracy
- Complete set of changing gear

Cutter 11 pieces set

- DIN 4971R DIN 4972R
- DIN 4973R DIN 4974R
- DIN 4975 DIN 4976
- DIN 4977R
- DIN 4978R
- DIN 4980L
- DIN 4980R
- DIN 4981R



S/N:10005

Quick change cutter rest



S/N:10011

Mill chuck set




Chuck dia. 4,6,8,10,12, 14,16mm

S/N:10148

Cutter 6 pieces set

- DIN 4972R DIN 4973R
- DIN 4974R DIN 4976R
- DIN 4977R
- DIN 4978R



S/N:10006

Tailstock chuck



Dia. 13mm+MT#2
 S/N:10012

Digital spindle speed readout



S/N:10030
 For mini lathe SC2

Cutter 5 pieces set

- DIN 4971R DIN 4975
- DIN 4980R
- DIN 4980L
- DIN 4981R



S/N:10004

Knurling tool holder



S/N:10130

Wood toolrest with center



S/N: 10064

Digital spindle speed readout (independent using)



S/N: 10062
 For mini Lathe C2

Cutter 2 pieces set



S/N:10016

Cut-off tool



S/N:10145

Rocker tool post



S/N:10136

OPTIONAL ACCESSORIES